



## Shortwave Half-Coated White Infrared Tube

Model	Voltage (V)	Wattage (W)	Heating length (mm)	Overall length (mm)	base	Appearance	Burning position	Service life (H)
LPC24875/235R7S	220-240	875	175	235	R7S	Transparent/ Reflection	Any Place	5000
LPC2410/355	220-240	1000	280	355	SK15	Transparent/ Reflection	Any Place	5000
LPC2412/226	220-240	1200	165	226	SK15	Reflection	Any Place	5000
LPC2415/226	220-240	1500	165	226	SK15	Transparent/ Reflection	Any Place	5000
LPC2420/355	220-240	2000	280	355	SK15	Reflection	Any Place	5000
LPC4020/355	380-400	2000	280	355	SK15	Transparent/ Reflection	Any Place	5000
LPC4020/490	380-400	2000	430	490	SK15	Reflection	Any Place	5000
LPC4025/355	380-400	2500	280	355	SK15	Transparent/ Reflection	Any Place	5000
LPC4025/380	380-400	2500	315	380	SK15	Reflection	Any Place	5000
LPC2430/355	220-240	3000	280	355	SK15	Transparent/ Reflection	Any Place	5000
LPC4030/35	380-400	3000	280	355	SK15	Reflection	Any Place	5000
LPC4030/380	380-400	3000	315	380	SK15	Transparent/ Reflection	Any Place	5000
LPC4030/490	380-400	3000	430	490	SK15	Reflection	Any Place	5000
LPC4030/790	380-400	3000	720	790	SK15	Transparent/ Reflection	Any Place	5000